

A RECEPTACLE HAVING A NECK PROVIDED WITH
TWO PORTIONS OF DIFFERENT DIAMETERS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 60/411,383 filed September 18, 2002. ~~The present invention relates to packaging and dispenser devices, in particular receptacles for containing cosmetics and applicators for fixing on such receptacles.~~

BACKGROUND OF THE INVENTION

[0002] The present invention relates to packaging and dispenser devices, in particular receptacles for containing cosmetics and applicators for fixing on such receptacles.

[0003] The term "cosmetic" is used herein to designate any "cosmetic product" as defined in EEC Council Directive 93/35/EEC of June 14, 1993.

[0004] At present, there exist hair-coloring kits including a flask containing an oxidizer, said the flask having a threaded neck of a certain diameter. ~~which,~~ ~~pPrior~~ prior to use, the flask is closed by a cap having a corresponding diameter. The cap is manufactured using a mold having a large number of recesses ~~and of a~~ cost that is relatively high.

[0005] Accessories, such as applicator combs, having a plurality of dispenser orifices are made available together with the flasks.

[0006] Sometimes, accessories cannot be made in such a manner as to be capable of being screwed onto the threaded neck of an existing flask ~~When,~~ because of their nature or for manufacturing reasons, ~~the accessories put on offer~~

~~cannot be made in such a manner as to be capable of being~~
~~screwed onto the threaded neck of an existing flask, It~~
is then necessary to make new flasks and new caps, which
means that new molds need to be made. In addition,
existing accessories can no longer be used on the new
flasks unless adapters are provided. This, but that leads
to extra costs and, in addition, ~~that~~ can lead to problems
of leakage or an ugly appearance.

~~OBJECTS AND SUMMARY OF THE INVENTION~~

[0007] The present invention seeks to ~~remedy~~ address
~~these these~~ drawbacks ~~in full or in part~~.

[0008] In one embodiment of its aspects, the present
invention, ~~thus provides~~ a receptacle is provided
comprising:

- a body, and

~~— a neck, comprising:~~

~~— The neck comprises a first portion having that~~
has a first diameter, in particular a first inside
diameter, and a having first fixing means, and

~~— a second portion situated located between the~~
body of the receptacle and the first portion. The, said
second portion ~~having has~~ a second diameter, ~~in particular~~
~~a second inside diameter~~, greater than the first diameter,
and ~~a having~~ second fixing means. The neck may have a
shoulder connecting the first portion to the second
portion. The shoulder may be a plane annular surface
extending outside and perpendicular to the neck. This
annular surface may be used, as described in greater
detail below, to cooperate with an accessory so as to
obtain sealing. The receptacle may be made of a plastic
material.

[0009] In one aspect of the present invention, the first portion or the second portion has a thread. In a further aspect, the first portion and the second portion both have threads, and still further, they have threads that allow for turning in the same direction.

[0010] In another aspect of the present invention, the first portion or the second portion has at least one snap-fastening shape in relief. The snap-fastening shape in relief may be an annular bead.

[0011] It is then possible to fix accessories of different kinds on the first and second portions of such a receptacle, e.g. by screw fastening or snap-fastening, depending on the nature of the fixing means.

[0012] By way of example, the first portion may be configured to receive existing accessories, that have having the same diameter as the neck of existing flasks. The, and the second portion may be configured, for example, to receive a newly-developed accessory that, which new accessory has an assembly skirt with presenting a relatively larger diameter. —Thus, the invention makes it possible to continue to be able to use existing caps, thus avoiding the need to make new molds for caps. —The invention also makes it possible to use a greater variety of accessories in association with a given receptacle, and without having to use adapters.

[0013] ~~In an embodiment of the invention, the neck has a shoulder, in particular an inside shoulder, connecting the first portion with the second portion. Such a shoulder may, for example, define a plane annular surface extending outside the neck, perpendicular to the axis thereof. This annular surface may be used, as described~~

~~in greater detail below, to co-operate with an accessory so as to obtain sealing.~~

[0014] At least one of the first and second portions may include a thread enabling an accessory to be screwed onto the neck of the receptacle. Such a thread may be made in various ways and may comprise, for example, a one-start thread or a multiple-start thread.

[0015] In a variant, ~~or in addition,~~ at least one of the first ~~and/or~~ second portions include a snap-fastening shape in relief comprising an annular bead, for example, enabling an accessory to be fixed onto the neck of the receptacle by snap-fastening.

[0016] Another aspect of the present invention allows the first portion to have a first inside diameter. The second portion has a second inside diameter that is larger than the first inside diameter.

[0017] In another aspect of the present invention, the neck has an inside shoulder that connects the first portion to the second portion.

~~— The neck of the receptacle may have first and second fixing means of the same type, both being constituted, for example, by snap-fastening means or by threads that enable screw fastening to be performed by turning in the same direction, or which may be of different types, the first fixing means being constituted by a thread, for example, with the second fixing means being constituted by snap-fastening means, or vice versa. — At least one of the first and second fixing means may also be configured, for example, so as to enable snap-fastening to take place after performing a screw fastening operation, such snap-fastening having the function, for example, of making~~

~~unscrewing more difficult, or merely of informing the user that the accessory has been screwed on far enough.~~

~~—The receptacle may advantageously be made of a plastics material.~~

[0018] In another ~~of its aspects of,~~ the present invention also provides a kit is provided. The kit comprising a receptacle with a first portion having a body and a neck including first portion with a first diameter and a first fixing means and a second portion located between the body and the first portion with a second diameter larger than the first diameter and a second fixing means.~~as defined above together with~~ The kit also includes at least one accessory configured to be fixed on the neck. ~~, e.g. by screw fastening.~~ ~~In an embodiment of the invention, t~~ The accessory is may be configured to cooperate with be fixed on the second portion, for example, e.g. by screw fastening.

[0019] The accessory may ~~then have an~~ assembly skirt configured to cooperate with fix on the second portion, e.g. for example, by screw fastening. The assembly, ~~said skirt may include~~including a sealing surface that abuts for coming to bear against a shoulder connecting which connects the first and second portions of the receptacle together. This sealing surface may be defined, for example, by an annular bead. ~~—~~ Sealing between the accessory and the receptacle can thus be provided on the outside of the neck, thus, in a further aspect, making it possible in particular for the accessory may to be made without a sealing lip that comes to bear against the inside of the neck of the receptacle. This makes it possible to use a manufacturing method for making the

accessory that is incompatible with the presence of such a sealing lip.

[0020] In an ~~embodiment~~ one aspect of the present invention, the accessory is ~~constituted by an~~ applicator, in particular an applicator comb. ~~—~~ The applicator may have teeth. ~~—with a~~ At least one of the teeth including may include at least one dispenser orifice which may be at a distance from the free end of that ~~e~~ corresponding tooth. The dispenser orifice ~~and which~~ may be oriented in such a manner as to limit the risk of dispensing the substance other than between the teeth. Such a configuration is particularly useful with an applicator comb since it makes it possible to avoid dispensing the substance directly onto the scalp, and it can make it easier to treat locks of hair.

[0021] In another ~~embodiment~~ aspect of the present invention, the applicator has at least one row of teeth with end teeth ~~situated~~ located at the ends of the row. ~~—~~ The end teeth do not having ~~have~~ any dispenser orifice opening ~~out~~ other than the ones that open into the gap between the teeth. The end teeth may ~~, or indeed not having~~ have any dispenser orifices at all.

[0022] In another aspect of the present invention, ~~A~~ at least one of the teeth ~~tooth~~ in the row ~~situated~~ located between the end teeth may have two dispenser orifices on the exterior of the tooth ~~opening out sideways~~ on opposite sides ~~of the tooth~~ in a direction parallel to the row. ~~—~~ In an ~~embodiment~~ further aspect of the present invention, each tooth ~~situated~~ located between the end teeth has at least one dispenser orifice. ~~—~~ The applicator may be made by molding a plastics material, and in one aspect, at least one of the teeth may include ~~be~~

~~provided with~~ at least one groove extending from its free end to a dispenser orifice formed in the tooth. ~~the groove enabling the tooth to be unmolded by separating two mold portions in a direction parallel to the axis of the tooth. This can make it simpler to manufacture the applicator.~~

[0023] In one aspect ~~an embodiment~~ of the present invention, the applicator has at least six teeth, each provided with at least one dispenser orifice. ~~and~~ preferably, each tooth has ~~with~~ two dispenser orifices opening ~~out~~ in opposite directions. ~~All of the teeth of the applicator may be of the same length.~~

[0024] When at least one of the first and second portions of the neck has a thread, the kit may include at least one accessory configured for screwing onto the thread. ~~Also, When~~ at least one of the first and second portions of the neck includes at least one snap-fastening shape in relief, the kit may include at least one accessory ~~provided~~ arranged with at least one complementary snap-fastening shape in relief configured to co-operate with the snap-fastening shape of the receptacle.

[0025] In another aspect ~~embodiment~~ of the present invention, the kit ~~has~~ includes at least two accessories of different kinds. ~~In particular, one accessory will cooperate with the designed to be fixed, e.g. by screw fastening, on the first portion and the other accessory will cooperate with the second portions of the neck, respectively. For example, One of the accessories may be constituted by a cap and the other by may be an applicator, for example by an applicator comb as defined above.~~

[0026] In one aspect, ~~T~~the kit may also have an accessory configured for cooperating with fixing, e.g. by ~~screw fastening, on the first or the second portion of the neck.~~ The accessory may also be being different from a cap or an applicator comb comprising a row of teeth, being constituted, for example, by a dispenser endpiece or by a receptacle.

[0027] The receptacle may be filled with a cosmetic. The cosmetic may be, for example, a substance for coloring the hair.

[0028] In another embodiment of ~~its aspects,~~ the present invention, ~~also provides~~ an applicator is provided that cooperates with ~~configured to be fixed, e.g. by screw fastening, on the neck of a receptacle.~~ The applicator including ~~includes~~ an assembly skirt configured arranged to cooperate with be fixed on the receptacle. The assembly skirt includes ~~and provided with~~ an annular bead made on an inside surface of the skirt at a distance from the free end ~~thereof.~~ Such an ~~The annular bead makes it possible to obtain sealing.~~ as mentioned above. In a further aspect of the present invention, an applicator fastens onto the neck of the receptacle by screw fastening.

[0029] In another ~~of its aspects~~ of the present invention, ~~also provides~~ a method is provided for of manufacturing a kit comprising a receptacle as defined above and at least one accessory configured for fixing, e.g. ~~by screw fastening,~~ on the neck, in particular an applicator comb. The ~~the method comprising~~ comprises the following steps:

- making the receptacle, ~~+~~
- ~~—~~filling the receptacle with a cosmetic~~+~~,

~~fixing a cap on the first portion of the neck, e.g. by screw fastening, and~~

~~packaging the receptacle carrying the cap with an applicator configured to be capable of being fixed on the second portion of the neck, e.g. by screw fastening.~~

[0030] In another embodiment of ~~its aspects,~~ the present invention, ~~provides a~~ receptacle comprising:— a body, and— a neck. The neck, comprising:— a first portion having a first inside diameter and including a first fixing means, and— a second portion situated between the body of the receptacle and the first portion. ~~The, said second portion having has~~ a second inside diameter greater than the first inside diameter, and ~~having has~~ a second fixing means.

[0031] In another of its aspects, the present invention provides a receptacle comprising:— a body, and— a neck, comprising:— a first portion having a first diameter and including a first fixing means and, — a second portion ~~situated located~~ between the body of the receptacle and the first portion. ~~The, said second portion having has~~ a second diameter greater than the first diameter, and ~~having has~~ a second fixing means. The first portion and the second portion are connected by an inside shoulder. ; and — an inside shoulder connecting the first portion to the second portion.

[0032] In still yet another of its aspects, the present invention provides a receptacle comprising:— a body, and— a neck, comprising:— a first portion having a first diameter and including a first thread, and— a second portion ~~situated located~~ between the body of the receptacle and the first portion. ~~The, said second portion having has~~ a second diameter greater than

the first diameter and ~~including~~ includes a second thread.
~~, the first and second threads enabling enable~~ screw fastening to be performed by turning in the same direction.

[0033] In another embodiment of the present invention, a receptacle is provided which includes a body and a neck. The neck includes a first portion having a first diameter and at least one of a first thread or a first snap-fastening shape in relief, and a second portion located between the body of the receptacle and the first portion. The second portion has a second diameter greater than the first diameter and at least one of a second thread or a second snap-fastening shape in relief.

[0034] In another of its aspects, the present invention provides a kit comprising:

- a receptacle comprising:

~~_____ a body, and~~

~~_____ a neck and at least two accessories of different kinds, comprising:~~

~~_____ The neck includes a first portion having a first diameter and including a first fixing means, and~~

~~_____ a second portion situated located between the body of the receptacle and the first portion. The said second portion having has a second diameter greater than the first diameter, and having a second fixing means, and~~

~~_____ at least two accessories of different kinds,~~

In a further aspect, the accessories are selected in particular from an applicator, an endpiece, and a cap, and a second receptacle.

[0035] In still another embodiment of its aspects, the present invention, provides a kit comprising:

- a receptacle comprising:
_____ a body, and
_____ a neck, and at least two accessories. _____,
comprising:
_____The neck includes a first portion having
a first diameter and including a first fixing means; and
_____ a second portion situated located
between the body of the receptacle and the first portion.
The, said second portion havinghas a second diameter
greater than the first inside diameter, and having a
second fixing means. The ; and
_____ at least two accessories for fixing to the
first and second portions respectively, the accessories
being selected in particular from an applicator and a
cap, cooperate with the first portion and the second
portion, respectively. In one aspect of the present
invention, the accessories are selected from an
applicator, an endpiece, a cap and a second receptacle.

BRIEF DESCRIPTION OF THE DRAWINGS

[0036] The invention can be better understood on reading the following detailed description of non-limiting embodiments and on examining the accompanying drawings, in which:

[0037] —Figure 1 is a diagrammatic and fragmentary axial section view showing a kit in accordance with a first embodiment of the present invention, the kit comprising a receptacle and a cap screwed onto the threaded first portion of the neck;

[0038] —Figure 2 is a diagrammatic and fragmentary axial section view showing a kit of the invention comprising the receptacle of Figure 1, the cap being

~~replaced by an applicator screwed onto the threaded second portion of the neck;~~

[0039] ~~—Figure 3 is a diagrammatic and fragmentary axial section view in another perspective of the Figure 2 kit.~~

[0040] ~~—Figure 4 is a diagrammatic and fragmentary detail view in axial section view of the top portion of one of the teeth of the applicator in the Figure 2 kit.~~

[0041] ~~Figure 5 is a diagrammatic and fragmentary axial section view of another example of a kit in accordance with the present invention, comprising the Figure 1 receptacle with a dispenser endpiece screwed onto its threaded first portion;~~

[0042] ~~Figure 6 is a diagrammatic and fragmentary axial section view of a kit constituting another embodiment aspect of the present invention, comprising the Figure 1 receptacle having the neck of a second receptacle screwed onto its threaded first portion;~~

[0043] ~~Figure 7 is a diagrammatic and fragmentary axial section view showing another aspect variant of the kit of Figure 1; and~~

[0044] ~~Figures 8 and 9 are diagrammatic and is a fragmentary axial section views showing still another aspect two variant embodiments of the present invention.~~

[0045] Figure 9 is a fragmentary axial view showing yet another aspect of the present invention.

~~MORE-DETAILED DESCRIPTION~~

[0046] ~~Figure 1 shows a kit 1 of the invention comprising a receptacle 2 and a closing cap 3. In the example described, the receptacle 2 is made of a plastics material. The receptacle 2 comprises a body 4~~

containing a cosmetic, for example a substance P for coloring the hair, and a neck 5 ~~of about~~ axis X.

[0047] At its top end, the neck 5 has a first portion 6 and at its bottom end it has a second portion 7. ~~The, the~~ second portion ~~being situated~~ is located between the body 4 and the first portion 6 and ~~presenting~~ has a diameter greater than the diameter of the first portion 6. The first portion may have a thread 28 ~~is provided~~ on its outside surface ~~in the example shown with a thread 28 and~~ and the second portion 7 may also have a thread 29 ~~is provided~~ on its outside surface ~~with a thread 29.~~ The threads 28 and 29 may be made in various ways, for example, a one-start thread or a multiple-start thread.

[0048] The first and second threaded portions 6 and 7 are connected together by a shoulder 8 defining a plane annular surface 9 which extends outwards from the neck 5 perpendicularly to the axis X.

[0049] The cap 3 has a tubular skirt provided with an inside thread 10. The inside thread 10 enables cap 3 ~~enabling it~~ to be screwed onto the threaded first portion 6 of the neck 5, as shown in Figure 1. Sealing between the neck 5 and the cap 3 ~~is~~ may be implemented by means of a sealing lip 11 of the cap 3 ~~3.~~ Sealing lip 11 ~~which~~ presses against the radially inner surface of the threaded first portion 6, which surface is circularly cylindrical about the axis X.

[0050] The neck of the receptacle may have first and second fixing means of the same type, as shown in FIG. 1, for example, threads. The threads enable screw fastening to be performed by turning. The threads may be turned in the same direction, or in different directions. Also first and second fixing means may be of different types.

For example, the first fixing means being constituted by a thread, and the second fixing means being constituted by snap-fastening means, or vice versa. At least one of the first and second fixing means may also be configured, for example, so as to enable snap-fastening to take place after performing a screw fastening operation. The snap-fastening may have the function, for example, of making unscrewing more difficult, or merely of informing the user that the accessory has been screwed on far enough.

[0051] To apply the substance P to the hair, the user unscrews the cap 3 and screws an applicator comb 15 onto the threaded portion 7, as shown in Figure 2. ~~_____~~ This applicator 15 is made as a single molding of plastics material. At its bottom end, the applicator 15 ~~it comprises~~ includes an assembly skirt 16, and about halfway up ~~it~~ applicator 15 comprises ~~includes~~ a transverse wall 17 having a row of teeth 18 extending therefrom.

[0052] This row 18 has two end teeth 19 with six intermediate or "active" teeth 20 being interposed between them. The teeth 20 may be ~~, and being~~ of the same length as the end teeth 19.

[0053] As shown in the example shown of Figure 2, the row 18 extends substantially along the entire diameter of the transverse wall 17. ~~_____ and~~ ~~t~~ The six intermediate teeth 20 extend over a length that is greater than the diameter of the threaded first portion 6.

[0054] Each intermediate tooth 20 ~~has~~ may have an internal channel 21 whose bottom end opens out through the transverse wall 17. The internal channel 21 ~~and which~~ communicates with the outside via two dispenser orifices 22. ~~_____ In the example shown,~~ As shown in Figures 2 through 4, each tooth 20 has two substantially parallel

side faces 23 perpendicular to the axis of the row 18. ~~and~~ The two dispenser orifices 22 open out respectively in said two side faces 23 at a non-zero distance from the free end of the tooth, ~~as can be seen in particular in Figures 2 to 4.~~

[0055] Grooves 25 extend in each face 23 of the tooth 20 from the dispenser orifice 22 present in said face to the free end of the tooth. The dispenser orifices 22 may be made by means of two mold portions that are movable relative to each other parallel to the longitudinal axis of the teeth 20. The mold portions, and that come into contact at the level of the dispenser orifices 22. The groove enables the tooth to be unmolded by separating two mold portions in a direction parallel to the axis of the tooth. This can make it easier to manufacture the applicator.

[0056] The end teeth 19 ~~do~~ may not have any dispenser orifices. ~~Thus,~~ the dispenser orifices 22 of the teeth 20 ~~always~~ open out into a gap lying between two teeth. ~~, thus making~~ This makes it possible to limit the risk of substance being squirted out from the row 18.

[0057] In its bottom portion, the assembly skirt 16 has an inside thread 26 enabling it to be screwed onto the threaded second portion 7 of the neck 5.

[0058] The assembly skirt 16 also has an annular bead 27 made on the inside surface of the skirt 16. The annular bead 27 is located, situated immediately above the inside thread 26 in the example shown. This annular bead 27 is designed to abut ~~bear against~~ the annular surface 9 of the neck 5, as shown in Figure 2. This will ~~so as to~~ provide sealing between the neck 5 and the applicator 15. ~~Because~~ sealing is provided on the

outside of the neck 5, it is possible to avoid the need to provide a sealing lip that bears against the inside surface of the threaded portion 6. ~~____, thus making~~ This makes it possible to provide the applicator 15 with active teeth 20 over a distance that is greater than the diameter of the threaded first portion 6. Also, it is possible ~~and thus~~ to provide a relatively large number of teeth, for example, six in the example shown.

[0059] In order to treat the hair, the user moves the applicator 15 through the hair with the substance P flowing out into the channels 21 leading to the dispenser orifices 22.

[0060] The receptacle 2 may be associated with accessories other than a cap 3 and an applicator comb 15.

[0061] By way of example, Figure 5 shows an accessory 30 constituted by an endpiece having a single dispenser orifice. Accessory 30 may be ~~, and suitable~~ for being screwed onto the neck 5 of the receptacle 2. ~~____~~ This endpiece ~~accessory~~ 30 comprises an assembly skirt 31 with an inside thread ~~suitable for being~~ which may be screwed onto the threaded first portion 6 of the neck 5. ~~____~~ The endpiece ~~accessory~~ 30 also comprises an internal sealing skirt 32 that ~~comes to bear against~~ may abut the inside surface of the threaded first portion 6. ~~____~~ At its top end, the ~~endpiece~~ accessory 30 is provided with a snap-off portion 33 which the user detaches at the moment of use.

[0062] It is also possible to use an accessory ~~constituted, by way of~~ for example, by such as a second receptacle 35, as shown in Figure 6. This allows one ~~, in order~~ to perform extemporaneous mixing of two substances, in particular, an oxidizer and a coloring agent, prior to application on the hair. ~~____~~ The second receptacle 35 has

a neck 36 with an inside thread configured for screwing onto the threaded first portion of the neck 5. Sealing can be obtained, for example, by pressing the end of the neck 36 against the annular surface 9. Annular, ~~which~~ surface 9 may be provided, where appropriate, with sealing means such as a deformable gasket.

[0063] ~~Without going beyond the ambit of the present invention,~~ In Figure 7, the cap 3, described with reference to Figure 1, may also be configured so as to be suitable for screwing onto the threaded second portion 7 of the neck 5, ~~as shown in Figure 7.~~ ~~In the examples described above,~~ The accessories are ~~can be~~ fixed by being screwed onto the neck 5 of the receptacle.

[0064] ~~It would not go beyond the ambit~~ With the scope of the present invention can be to provide other fixing means can be provided on the outside surfaces of the portions 6 and 7 of the neck 5. ~~By way of~~ For example, Figures 8 and 9 show a receptacle provided with a neck 5' that differs from the above-described neck 5 in that the threads of the first and second portions 6 and 7 are replaced by annular beads 40 and 41, respectively. ~~The accessories such as a cap 3' and an applicator 15', for example, are then each provided with a respective annular groove 42, 43 suitable for co-operating with the corresponding annular bead 40 or 41 by snap-fastening.~~

[0065] Naturally, the invention is not limited to the examples described above. ~~In particular,~~ the applicator comb 15 may be replaced by any other type of applicator, for example, ~~e.g.~~ having teeth without any dispenser orifices or with the dispenser orifices being made at the base of the teeth, ~~for example.~~

[0066] Throughout the description, including in the claims, the term "comprising a" should be understood as being synonymous with "comprising at least one" unless specified to the contrary.

[0067] Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

452834_1.DOC

A-B-S-T-R-A-C-T

~~The present invention provides a receptacle comprising:~~

- ~~— a body; and~~
- ~~— a neck, comprising:~~
 - ~~— a first portion having a first diameter, and having first fixing means; and~~
 - ~~— a second portion situated between the body of the receptacle and the first portion, said second portion having a second diameter greater than the first diameter, and having second fixing means.~~

The present invention provides a receptacle including a body and a neck. The neck includes a first portion having a first diameter and a first fixing means. The neck also includes a second portion located between the body and the first portion. The second portion has a second diameter that is greater than the first diameter and a second fixing means.